

Smart Fieldmeter® Digital, Model: RFP-05



- Bright color OLED display with good visibility can be set to display only the information important to the user.
- Portable lightweight design with detachable isotropic probe and two-cell AA primary or rechargeable battery offers flexibility and advantages in the field.

EMC Test Design, LLC®
P.O. Box 600532,
Newton, MA 02460, USA.
www.emctd.com,
exid@emctd.com,
508-292-1833.

Smart Fieldmeter® Digital RFP-05

- Electromagnetic field monitor having flexible and expandable architecture, state of the art design with convenience and simplicity for users on a budget.

Main Features

- Operates with and stores the data of multiple probes, both current and future models.
- Large dynamic range with auto-ranging and auto-zero functions offers high accuracy and simple operation.
- Advanced programmable data sampling with time and space averaging allows monitoring and recording of time variable signals.
- Internal data logging with removable flash memory card offers programmable and practically unlimited data storage.
- Serial bidirectional data port and IR remote control for PC data transfer and wireless instrument control.



System Parameters

Meter RFP-05 with probes:

Probe PI-01:	0.2 MHz - 3 GHz. 0.2 - 600 V/m.
Probe PI-03:	3 MHz - 18 GHz. 0.8 - 800 V/m.
Probe PI-01V:	800 -1900 MHz. 0.4 - 600 V/m.